The United States of America



The Commissioner of Patents and Trademarks

Has received an application for a patent for a new and useful invention. The title and description of the invention are enclosed. The requirements of law have been complied with, and it has been determined that a patent on the invention shall be granted under the law.

Therefore, this

United States Patent

Grants to the person(s) having title to this patent the right to exclude others from making, using, offering for sale, or selling the invention throughout the United States of America or importing the invention into the United States of America for the term set forth below, subject to the payment of maintenance fees as provided by law.

If this application was filed prior to June 8, 1995, the term of this patent is the longer of seventeen years from the date of grant of this patent or twenty years from the earliest effective U.S. filing date of the application, subject to any statutory extension.

If this application was filed on or after June 8, 1995, the term of this patent is twenty years from the U.S. filing date, subject to any statutory extension. If the application contains a specific reference to an earlier filed application or applications under 35 U.S.C. 120, 121 or 365(c), the term of the patent is twenty years from the date on which the earliest application was filed, subject to any statutory extension.

Buce Tehran
Commissioner of Patents and Trademarks

Melvinia Gary



United States Patent [19]

Wei-Hwang

[56]

[11] Patent Number:

5,718,090

Date of Patent:

Feb. 17, 1998

[54]	PRESTRESSED CONCRETE TENSIONING SYSTEM
[76]	Inventor: Lin Wei-Hwang, 7F-2, No. 95-8 Chang Ping Rd. Sec. 1, Taichung, Taiwan
[21]	Appl. No.: 669,051
[22]	Filed: Jun. 24, 1996
[51]	Int. CL ⁶ E04C 3/26; E04C 5/08; E04B 1/38

[52] U.S. Cl. 52/223.14; 264/228; 264/229; 264/136 R; 264/122.6

. 52/223.1, 223.13, [58] Field of Search 52/223.14; 24/122.6, 136 R; 264/228, 229

References Cited

U.S. PATENT DOCUMENTS

4,362,421	12/1982	Kelly 264/228 X
4,507,008		Adl et al 24/122.6 X
4,641,816	2/1987	Kishida et al 24/136 R X
4,744,691		Thal 24/136 R X
4,888,922	12/1989	Lancelot 52/223.1 X
4,936,006	6/1990	Creedon 264/228 X
5,022,780	6/1991	Shaw 24/122.6 X
5,136,755	8/1992	Shaw 24/122.6

5,342,568 8/1994 Yokota 5,369,849 12/1994 De France 24/136 R

Primary Examiner—Carl D. Friedman
Assistant Examiner—Yvonne Horton-Richardson

[57]

A prestressed concrete tensioning system for a tensioning tendon in the construction of a prestressed concrete beam comprising an anchor seat and a prestressed tensioning device. The anchor seat embedded in one end of the beam and has spherical structure and inverse ratchet gripping device therein for adjustably holding one end of the tendon. The tensioning device has a hollow cylindrical housing including a hydraulic fluid chamber therein for slidably disposing a piston member in associated with a wedged surface grip means which are operated by hydraulic pressure for gripping and tensioning one end of the tendon, and a hemisphere concave in the forward end of the housing for engaging with the hemisphere convex of the anchor seat to obtain an universal joint effect. This disclosure is characterized in the prevention of shear and strength declination to the tendon and the risk to the ambient personnel. A supplemental tensioning device is provided to give greater flexibility to the prestressed concrete tensioning operation.

4 Claims, 5 Drawing Sheets

