

ACF

17569-DA

CE

Ø175x69mm (Ø6.89"x2.72")




IMPELLER	Plastic
BEARING	Ball
INSULATION	Class F
TERMINATION	Lead Wire
OPERATING TEMPERATURE	-20°C to + 70°C
DIELECTRIC STRENGTH	10M Ω min. @500 VDC
INSULATION RESISTANCE	1,800 VAC for 1 second
MOTOR TYPE	AC Induction Capacitor Motor
SAFETY	Thermally Protected
WEIGHT	870 g
ROHS COMPLIANCE	Yes
IP LEVEL	IP54 (Special IP Rating On Request)

175mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
ACF17569V2H2P-DA	230	0.22/0.28	52/64	2600/2900	1.10/1.46	28/37	294/313	8.33/8.86	66/68
ACF17569V1H2P-DA	115	0.48/0.54	53/63	2600/2900	1.10/1.46	28/37	294/313	8.33/8.86	66/68

DIMENSION



AIR PERFORMANCE

