AFS 50-TC





HOUSING
IMPELLER
BEARING
INSULATION
OPERATING TEMPERATURE

OPERATING VOLTAGE RANGE

DIELECTRIC STRENGTH
INSULATION RESISTANCE
SAFETY
MOTOR TYPE
ROHS COMPLIANCE
IP LEVEL

Metal/Aluminum Aluminum,Ø50mm Ball or Sleeve

Class B 0°C to + 45°C

85 VAC to 125 VAC for 115V Type 185 VAC to 245 VAC for 230V Type

1,500 VAC for 1 second 1,000 VAC for 1 second 10M Ω min. @500 VDC


Impedance Protected Shaded Pole Motor

Special IP Rating On Request

SPECIFICATION

	MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE
						inchH2O	mmH2O	CFM	m3/min	dB(A) @1M
	⊚AFS50660V2H-TC	220		45	1800			188	5.3	52

DIMENSION





	MODEL NO	DIMENSION(mm)							
l	MODEL NO.	L	L1	L2	L3	L4	L5	L6	
ĺ	AFS50660-TC	300	308	735	760	28	70	70	

AIR PERFORMANCE

