

D

8038D-TK

CE

80x80x38mm(3.14"x3.14"x1.49")




HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball
OPERATING TEMPERATURE	-10°C to +70°C
DIELECTRIC STRENGTH	5mA Max. at 500 VAC for 1 minute
INSULATION RESISTANCE	10M &omg; min. @500 VDC
WEIGHT	223 g
ROHS COMPLIANCE	Yes
IP LEVEL	Special IP Rating On Request

80 mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
D8038V48HBD-TK	48	0.9	43.2	15000	5	127	129.22	3.66	78.7
D8038V12HBD-TK	12	3.6	43.2	15000	5	127	129.22	3.66	78.7
D8038V24HBD-TK	24	1.8	43.2	15000	5	127	129.22	3.66	78.7

DIMENSION



SYMBANG

AIR PERFORMANCE

