


ECP

270220V2HB-CE

L01

270x245.5x101.3mm(10.5"x9.6"x4")



HOUSING	Engineer PP Plastic
IMPELLER	Axial Flow Type, ABS Plastic
BEARING	Ball
MOTOR TYPE	Single Phase Ball Bearing Motor
TERMINATION	Lead Wire
OPERATING VOLTAGE RANGE	100 VAC ~ 125 VAC for 115V Type 200 VAC ~ 245 VAC for 230V Type
DIELECTRIC STRENGTH	1500 VAC for 1 second
INSULATION	Class B
INSULATION RESISTANCE	10M Ohms min. @500VDC
OPERATING TEMPERATURE	-20°C to + 60°C
SAFETY	Thermally Protected
WEIGHT	2000 g
ROHS COMPLIANCE	Yes


270

mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
ECP270220V2HB-L01	230	1.27	168	3250	3.82	96.9	677.27	19.17	70

DIMENSION



Unit : mm

AIR PERFORMANCE

