

A

6030-FF

CE

60x60x30mm(2.36"x2.36"x1.18")



HOUSING	Aluminum Die Casting, Painted Black
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball
OPERATING TEMPERATURE	-20°C to +70°C
INSULATION	Class A
OPERATING VOLTAGE RANGE	103 VAC to 126 VAC for 115V Type 207 VAS to 253 VAC for 230V Type
DIELECTRIC STRENGTH	5mA Max. at 1500 VAC for 1 second
INSULATION RESISTANCE	10M Ω min. @500 VDC
MOTOR TYPE	Shaded Pole Motor
SAFETY	Impedance Protected
TERMINATION	Lead wire
WEIGHT	145g
IP LEVEL	IP44 (Special IP Rating On Request)


60mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
A6030V2H-FF	220	0.02/0.04	7.0/5.0	2300/2700	0.06/0.11	1.6/2.7	7.9/10	0.22/0.28	27/28
A6030V1H-FF	110	0.08/0.1	7.0/5.0	2300/2700	0.06/0.11	1.6/2.7	7.9/10	0.22/0.28	27/28

SYMBANG

DIMENSION



Unit : mm [inch]

AIR PERFORMANCE

