A 150550VM-DA (5.9"x6.77"x2.17")



HOUSING
IMPELLER
BEARING
OPERATING TEMPERATURE
INSULATION
OPERATING VOLTAGE RANGE


DIELECTRIC STRENGTH INSULATION RESISTANCE MOTOR TYPE SAFETY TERMINATION WEIGHT ROHS COMPLIANCE DUAL VOLTAGE IP LEVEL

Aluminum Die Casting, Painted Black							
Metal							
Ball							
-10°C to + 70°C							
Class A							
85 VAC to 125 VAC for 115V Type							
185 VAC to 245 VAC for 230V Type							
5mA Max. at 1500 VAC for 1 second							
$10M \ \Omega$ min. @500 VDC							
Outer Rotor, AC Induction Capacitor Motor							
Thermally Protected							
Lead Wire							
840 g							
Yes							
115/230 VAC							
IP54 (Special IP Rating On Request)							

SPECIFICATION

MODEL NO.	RATED RATED VOLTAGE(V) CURRENT(A)	RATED	INPUT	SPEED	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A)
MODEL NO.		POWER(W)	(RPM)	inchH2O	mmH2O	CFM	m3/min	@1M	
A15055DVHBLM-D	A 115	0.23/0.25	27/28	2750/3150	0.49/0.53	12.5/13.5	210/240	5.9/6.7	57/61

DIMENSION





+

Dual Voltage Wire Diagram

