

DCF

22599

CE

Ø225x99mm(Ø8.84"x3.89")




MOTOR	Outer rotor motor Ø92mm
IMPELLER	Plastic Impeller, Metal Plate
BEARING	Ball
OPERATING TEMPERATURE	-20°C to + 60°C
INSULATION RESISTANCE	10M Ω min. @500 VDC
DIELECTRIC STRENGTH	5mA Max. at 500 VAC for 1 minute
WEIGHT	1.81 Kg
ROHS COMPLIANCE	Yes
IP LEVEL	IP21 (Special IP Rating On Request)

225mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
DCF22599V24H	24	4.6	110.4	2700	2.03	50.5	687.9	19.47	68
DCF22599V48SH	48	4.0	192.0	3100	3.22	81.9	757.0	21.42	76
DCF22599V48H	48	2.3	110.4	2700	2.03	50.5	687.9	19.47	68

DIMENSION



Wiring Diagram

- Red — +VDC
- Blue — GND
- Yellow — 0-10V/PWM Speed Control
- White — Tachometer (FG)

SYMBANG

AIR PERFORMANCE

