


D7025



70x70x25mm(2.76"x2.76"x0.98")



HOUSING	Thermoplastic PBT, UL94V-0
IMPELLER	Thermoplastic PBT, UL94V-0
BEARING	Ball or Sleeve
OPERATING TEMPERATURE	-10°C to + 60°C
DIELECTRIC STRENGTH	5mA Max. at 500 VAC for 1 minute
INSULATION RESISTANCE	10M Ω min. @500 VDC
WEIGHT	85 g
ROHS COMPLIANCE	Yes
IP LEVEL	IP21 (Special IP Rating On Request)


70 mm

SPECIFICATION


MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
D7025V12SH	12	0.62	7.44	6000	0.55	14	54	1.53	48
D7025V12H	12	0.52	6.24	5500	0.45	11.49	49.36	1.4	45
D7025V12M	12	0.33	3.93	5000	0.39	9.88	45.31	1.28	30

DIMENSION

ROTATION DIRECTION



AIR FLOW



UNIT: mm[inch]

AIR PERFORMANCE

